

CS-CV310-A0-1C2WFR

1080P Outdoor Smart IP Camera

Introduction


EZVIZ products have been designed for your entertainment, communication and security. When you install the EZVIZ APP on your smartphone or tablet, EZVIZ devices will be connected to the cloud via their QR code and will immediately be online. With EZVIZ, you can watch your child's progress when you are away, keep an eye on your home, interact with your four-legged friends and prevent household accidents.



Main Features



FHD 1080P



Infrared Night Vision
(Up to 30 meters)



Strong Wi-Fi signal with two antennas



AP hot spot (LAN live view)



Audio pickup
(Up to 5 meters)



Support 2.4GHz Wi-Fi
(IEEE802.11b, 802.11g, 802.11n)




Support Micro SD card
(Max. 256G)



IP66 Dust and Water Protection

Dimension



Specifications

| | |
|-----------------------------|---|
| Model | CS-CV310-A0-1C2WFR |
| Camera | |
| Image sensor | 1/2.9" Progressive Scan CMOS |
| Minimum illumination | 0.02 lux @(F2.0,AGC ON) ,0 Lux with IR |
| Shutter Speed | Self-adaptive shutter |
| Lens | 4mm@ F2.0, view angle:81° (Horizontal), 94°(Diagonal) |
| Lens Mount | M12 |
| Day & Night | IR cut filter |
| DNR | 3D DNR |
| WDR | Digital WDR |
| Compression | |
| Video Compression | H.264 |
| H.264 Type | Main Profile |
| Video Bit Rate | Ultra-HD; HD; Standard. Adaptive bit rate. |
| Image | |
| Max. Resolution | 1920 × 1080 |
| Frame Rate | Max: 30fps; Self-Adaptive during network transmission |
| Network | |
| Smart Alarm | Motion detection |
| Wi-Fi Pairing | AP Pairing |
| Protocol | EZVIZ Cloud Proprietary Protocol |
| Interface Protocol | EZVIZ Cloud Proprietary Protocol |
| General Function | Anti-Flicker, Dual-Stream, Heart Beat, Password Protection, Watermark |
| Max. Bitrate | 2M |
| Interface | |
| Storage | Micro SD card slot (Max. 256G) |
| Wired network | RJ45 × 1 (10M/100M Adaptive Ethernet Port) |
| Wi-Fi | |
| Standard | IEEE802.11b, 802.11g, 802.11n Draft |
| Frequency Range | 2.4GHz ~ 2.4835 GHz |
| Channel Bandwidth | Support 20MHz |
| Security | 64/128-bit WEP, WPA/WPA2, WPA-PSK/WPA2-PSK |
| Transmission Rate | 11b: 11Mbps,11g: 54Mbps,11n: 144Mbps |
| General | |
| Operating Conditions | -22°F to 140 °F (-30°C ~ 60°C); Humidity 95% or less (non-condensing) |
| Power Supply | DC 12V/1A |
| Power Consumption | Max. 6W |
| IP Grade | IP66 |
| IR Range | Max. 30 meters(98.43ft). |
| Dimensions | 72mm × 72mm × 150mm(2.83 " × 2.83 " × 5.91 ") |
| Packaging Dimensions | 252mm × 110mm× 92mm(9.92 " × 4.33 " × 3.62 ") |
| Suttle Weight | 288g(0.63lbs) |