

UniFi6 Mesh





Mechanical

| Dimensions | Ø48.5 x 159.5 mm (Ø1.91 x 6.28") |
|---------------------|----------------------------------|
| Weight | 400 g (0.88 lb) |
| Enclosure materials | Plastic, aluminum |
| Mount material | Plastic |
| Weatherproofing | IPX5 |

Hardware

| Management interfaces | Ethernet Bluetooth | | |
|-------------------------|---|---|--|
| Networking interface | (1) GbE RJ45 port | | |
| Button | Factory reset | | |
| LED* | White/blue "Due to chip supply shortages, the U6 AP's LED has | peen limited to only white and blue color modes. | |
| Power method | РоЕ | | |
| Power supply | UniFi PoE switch 48V, 0.32A PoE adapter (include | d) | |
| Supported voltage range | 44 to 57VDC | | |
| Max. power consumption | 11.4W | | |
| Max. TX power | 2.4 GHz | 22 dBm | |
| | 5 GHz | 26 dBm | |
| MIMO | 2.4 GHz | 2 x 2 (UL MU-MIMO) | |
| | 5 GHz | 4 x 4 (DL/UL MU-MIMO) | |
| Throughput rate | 2.4 GHz | 573.5 Mbps | |
| | 5 GHz | 4.8 Gbps | |
| Antenna gain | 2.4 GHz | 3 dBi | |
| | 5 GHz | 5 dBi | |
| Mounting | Wall, desktop, pole mount (include Ceiling mount (optional) | Wall, desktop, pole mount (included) Ceiling mount (optional) | |
| Operating temperature | -30 to 60° C (-22 to 140° F) | -30 to 60° C (-22 to 140° F) | |
| Operating humidity | 5 - 95% noncondensing | 5 - 95% noncondensing | |
| Certifications | CE, FCC, IC | | |

Software

| WiFi standards | 802.11a/b/g WiFi 4/WiFi 5/WiFi 6 |
|-------------------|---|
| Wireless security | WPA-PSK, WPA-Enterprise (WPA/WPA2/WPA3) |
| BSSID | 8 per radio |
| VLAN | 802.10 |



| Advanced QoS | Per-user rate limiting |
|-------------------------|---|
| Guest traffic isolation | Supported |
| Concurrent clients | 300+ |
| Zero wait DFS | Yes* *Supported with upcoming firmware versions |

Supported Data Rates

| 802.11a | 6, 9, 12, 18, 24, 36, 48, 54 Mbps |
|-------------------|---|
| 802.11b | 1, 2, 5.5, 11 Mbps |
| 802.11g | 6, 9, 12, 18, 24, 36, 48, 54 Mbps |
| 802.11n (WiFi 4) | 6.5 Mbps to 600 Mbps (MCS0 - MCS31, HT 20/40) |
| 802.11ac (WiFi 5) | 6.5 Mbps to 3.4 Gbps (MCS0 - MCS9 NSS1/2/3/4, VHT 20/40/80/160) |
| 802.11ax (WiFi 6) | 7.3 Mbps to 4.8 Gbps (MCS0 - MCS11 NSS1/2/3/4, HE 20/40/80/160) |

