

## **DS-PKF201-WE** **Wireless Keyfob**



- Remote arming and disarming
- Configurable I and II buttons can provide more useful functions
- Frequency hopping against jamming for reliable transmission

## ▪ Specification

Communication	
Transmission technology	868.0-868.6 MHz
Transmission range (free space)	Up to 900 m
Maximum effective radiated power (ERP)	10 mW max
Radio signal modulation	2GFSK
Hardware features	
Number of buttons	Four buttons
Configuration of buttons	I key II key
Electrical characteristics	
Power supply	1 × CR2032 battery
Power consumption	max current: 40 mA quiescent current: 0.4 uA
Battery life	Up to 2 years (standby time)
General	
Operation temperature	-10 °C to 55 °C (14 °F to 131 °F)
Operation humidity	10% to 90%
Dimension (W×H×D)	35 × 64 × 11.2 mm
Weight	15 g

## ▪ Available Model

DS-PKF201-WE

**Headquarters**

No.555 Qianmo Road, Binjiang District,  
Hangzhou 310051, China  
T +86-571-8807-5998  
[www.hikvision.com](http://www.hikvision.com)



Follow us on social media to get the latest product and solution information.



Hikvision



HikvisionHQ



HikvisionHQ



Hikvision\_Global



Hikvision  
Corporate Channel



hikvisionhq