

MAXHUB Capture System

Capture Host

Model: CSP30M

Experience unparalleled integration with the CSP30M Capture Host, designed to seamlessly mesh localized capturing with online live streaming, meeting the diverse and dynamic needs of today's teaching scenarios.



High Integration

Seamlessly integrates localized capturing, online live streaming, and other functions to meet diverse teaching scenarios with ease.



Intelligent Control

Instantly captures images with a single touch on the full-laminated capacitive touchscreen, which intelligently identifies external video and audio equipment without the need for additional matching or adjustments.



Multi-Image Capture

Simultaneously captures images from 7 different channels, including main view, courseware, teacher panoramic view, teacher close-up, student panoramic view, student close-up, and board view.



Customizable Broadcasting

Allows customizable output views and precise human model recognition for automated broadcasting. Seamlessly integrates with mainstream video conferencing systems and live streaming platforms, enabling effortless live broadcasts.

I/O Port		Video	
DC In	×1	Video Recording Frame Rate	60 fps/ 30 fps/ 25 fps
RJ45	×5 (one for Internet, one for mic in, three for PoE)	Video Recording Resolution	1080p, 720p, VGA, QVGA
HDMI Out	×3	Video Recording Format	MP4
HDMI In (HDMI 1.4)	×2	Multi-Channel Recording	Up to 7 channels
USB-A 2.0	×1	Live Streaming Channel	Up to 3 RTMP channels, 1080p
USB-A 3.0	×2	Live Streaming Resolution	1080p, 720p, VGA, QVGA
USB Type-C	×2	Other Parameters	
RS422	×1		
Mic In	×1		
Line In	×1		
Line Out	×2	Storage	1TB SATA

Physical Parameters		Accessories	
Dimension (with stand, L × W × D)	374.9 × 270.5 × 46.1 mm	Power Adapter	×1
Dimension (without stand, L × W × D)	374.9 × 237.5 × 41.7 mm	Power Cable	×1
Shipping Dimension (W × H × D)	1 pc: 488 × 409 × 110 mm 4 pcs: 491 × 471 × 449 mm	Audio Cable	×1
Net Weight	2.85 kg	Phoenix Connector	×2
Gross Weight	1 pc: 4.85 kg 4 pcs: 21.70 kg	Anti-Trp Bracket	×1
		External Antenna	×5
		Wall Mount Bracket	×1
		Cable Cover	×1
		Screw Package	×1

Electrical Parameters		Environmental Conditions	
Power Adapter	100-240~50/60HZ 1.8A max	Operating Temperature	0°C ~ 40°C
Power Supply	DC 24V 3.33A	Storage Temperature	-20°C ~ 60°C
Power Consumption (standby)	≤ 0.5W	Operating Humidity	10% ~ 90% RH
		Storage Humidity	10% ~ 90% RH
		Altitude	Below 5000 meters

Statement

Size and weight vary by configuration and manufacturing process, please refer to the actual product.

The product images are for illustrative purposes only and may slightly differ in appearance, colour, size, etc. from the actual product.

The description, illustrations, etc. in this document may subject to change in accordance with the latest product specification and performance.

Should the above-mentioned change in the document become necessary, the document may be updated without written notice.